

Союз Советских
Социалистических
Республик



Получено в
г. Москва
по заявке № 070383
от 07.08.83

О П И С А Н И Е ИЗОБРЕТЕНИЯ

К АВТОРСКОМУ СВИДЕТЕЛЬСТВУ

(51) Дополнительное к авт. свид-ву -

(22) Заявлено 02.11.81 (21) 3352116/22-03

с присоединением заявки № -

(23) Приоритет -

Опубликовано 07.03.83. Бюллетень № 9

Дата опубликования описания 07.03.83

(11) 002514

(54) М. Кл.

E 21 B 29/10

(53) УДК 622.249.
4(088.8)

(72) Авторы
изобретения

В.П. Масич, А.А. Цыбин, В.А. Гайдаровский, Ш.Н. Курманжи
и В.В. Трофимов

(73) Заявитель

Всесоюзный орден Труда... основного значения
научно-исследовательский институт буровой техники

(54) УСТРОЙСТВО ДЛЯ УСТАНОВКИ ПЛАСТЫРЯ
В СКВАЖИНЕ

1

2

Изобретение относится к бурению и эксплуатации нефтяных и газовых скважин, а именно к устройству, позволяющему для перекрытия мест повреждения, образовавшихся в скважине, использовать пластину.

Известно устройство для установки пластины в обсадной колонне, включающее обсадную колонну, в которой установлена пластина, и закрепленную на ней головку гидравлической поршневой головки с направляющим выносом и конусом [1].

Однако применение указанного устройства связано с значительными трудностями по извлечению обсадной колонны из скважины. Последнее объясняется тем, что при недостаточной прочности предварительного сцепления пластины с колонной при протяжке обсадной колонны труба она может отделиться и место повреждения останется не перекрытым.

Наиболее близким к изобретению является устройство для установки пластины в скважине, включающее полый перфорированный корпус, с закрепленным на нем эластичным трубчатым элементом, расширяемый пластина и узел

фиксации пластины от продольного перемещения [2].

Недостатком данного устройства является низкая надежность в работе, связанная с несовершенством конструкции узла фиксации пластины. Это может привести к полной расщепке пластины и заклиниванию всего устройства в скважине.

Цель изобретения - повышение надежности работы устройства.

Указанная цель достигается тем, что в устройстве для установки пластины в скважине, включающем полый перфорированный корпус с закрепленным на нем эластичным трубчатым элементом, расширяемый пластина и узел фиксации пластины от продольного перемещения, последний выполнен в виде подпружиненных упоров и аксиальных втулок внутри корпуса с радиальными отверстиями с седлом для образующего шара и выступами на наружной поверхности, при этом корпус имеет сквозные радиальные отверстия для размещения в них подпружиненных упоров, установленных в плоскости выемки втулки.

На фиг. 1 изображено устройство, в транспортном положении, общий вид; на фиг. 2 - разрез А-А на фиг. 1;

на фиг. 3 - разрез Б-В на фиг. 1; на фиг. 4 и 5 - устройство в рабочем положении; на фиг. 6 - то же, после окончания работы.

Устройство (фиг. 1) состоит из составного полого перфорированного корпуса 1 с надетым на него эластичным трубчатым элементом 2. Поверх эластичного элемента 2 помещен расширяемый пластырь 3, изготовленный из антикоррозионного металла, обладающего необходимыми прочностными и упругими свойствами, например, нержавеющей стали.

Эластичный трубчатый элемент 2 крепится к корпусу 1 при помощи муфт 4. В верхней части корпуса 1 имеется резьба для подсоединения переходника 5. Верхняя часть составного корпуса, имеющая радиальные отверстия а и б, снизу оканчивается крышкой 6 с калиброванными отверстиями в.

Узел фиксации пластыря 3 от продольного перемещения выполнен в виде втулки 7 с седлом 2, выемками д и г, и пружиной 8, насаженной на наружную поверхность. В сквозных отверстиях б корпуса 1 расположены упоры 8, снабженные пружинками 9. На упоры 8 опирается пластырь 3 при спуске устройства в скважину. Втулка 7 удерживается от самопроизвольного перемещения срезной шпилькой 10. Ограничителем перемещения втулки 7 служит срезной элемент 11, установленный в нижней части корпуса 1.

Устройство работает следующим образом.

После спуска устройства на буровых или насосно-компрессорных трубках в скважину на необходимую глубину в трубу забрасывается шар 12, который садится в седло 2 втулки 7 и перекрывает в ней центральный канал (фиг. 4). Под действием давления закачиваемой жидкости эластичный элемент 2 расширяется и входит в контакт с пластырем 3. При достижении определенного давления во внутренней полости труб и эластичного элемента 2 пластырь 3 деформируется и прижимается к стенкам скважины, перекрывая место повреждения обсадной колонны или зону поглощения жидкости. В случае ликвидации повреждения обсадной колонны по концам оболочки 3 в расточках помещаются резиновые уплотнительные кольца, обеспечивающие герметичность пластыря.

После того, как участок пластыря 3, контактирующий с рабочей частью эластичного элемента 2, прижмется к стенке скважины, давление жидкости в трубах повышается до такой величины, при которой срезная шпилька 10 разрушается. При этом втулка 7 перемещается вниз до упора в срезной эле-

мент 11 (фиг. 5). Преждевременный срез элемента 11 при перемещении втулки 7 исключается за счет того, что дросселирование жидкости, вытекающей из корпуса 1 через калиброванную втулку 7 через калиброванное отверстие в крышке 6, создает гидравлический демпфер, который обеспечивает плавное без удара перемещение втулки 7. При этом положении втулки 7 (фиг. 5) выемки д оказываются против упоров 8. Под действием пружин 9 упоры 8 перемещаются внутрь корпуса 1 и утапливаются в выемках д втулки 7 (фиг. 5). Для деформации и герметичного прижатия к стенке скважины нижней части пластыря 3 давление в трубах снижает, эластичный трубчатый элемент 2 приобретает первоначальную форму, затем устройство приспускают на определенную величину. Нагнетая в трубы жидкость и повышая ее давление до известного предела, производят деформацию нижней части пластыря 3. После окончания операции по установке пластыря перед подъемом инструмента на поверхность давление жидкости в трубах повышают до срезаания шпильки 10, при этом втулка 7 перемещается в крайнее нижнее положение (фиг. 6). Дав в втулку 7 совмещается с радиальными отверстиями в в корпусе 1 и внутренняя полость труб сообщается с затрубным пространством, что обеспечивает одорожение труб при подъеме инструмента. Упоры 8 остаются в таком положении, при котором может быть осуществлен беспрепятственный подъем инструмента на поверхность. Переместив втулку 7 в крайнее верхнее положение и заменив срезные элементы 10 и 11 на новые, готовят устройство для проведения следующих операций по установке пластырей в скважинах. Для удобства сборки элемент 10 можно устанавливать в корпус 1 под втулкой 7.

Удерживание пластыря 3 при спуске инструмента в скважину осуществляется при помощи узла (элементы 7 - 9), размещенного в нижней части корпуса 1 (фиг. 1) и калибруемого оптимальным образом. Кроме указанного, могут быть применены два узла, отличающихся по конструктивному исполнению и размещенных в верхней и нижней части корпуса 1. Возможен и такой вариант удерживания оболочки 3, при котором используется описанный узел, размещенный в нижней части корпуса и разрушаемый штифт, фиксирующий оболочку 3 в верхней ее части. Разрушение штифта и освобождение оболочки 3 может быть осуществлено либо при деформации эластичного элемента 2, либо при перемещении втулки 7.

1002514

Применение предложенного устройства позволяет увеличить надежность операции по ликвидации перегретых жидкостей или жидкостей, находящихся под давлением, за счет использования надежного сцепления ленточной системы со стенками емкости. Кроме того, использование возможности изготовления на специализированном оборудовании короткосторонних гофрированных ленточных пластин.


Таким образом, технически экономически выгодно использовать предложенное устройство для ликвидации перегретых жидкостей или жидкостей, находящихся под давлением, за счет использования надежного сцепления ленточной системы со стенками емкости.

Ссылки на prior art



Устройство для ликвидации перегретых жидкостей или жидкостей, находящихся под давлением, за счет использования надежного сцепления ленточной системы со стенками емкости.

5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190 195 200 205 210 215 220 225 230 235 240 245 250 255 260 265 270 275 280 285 290 295 300 305 310 315 320 325 330 335 340 345 350 355 360 365 370 375 380 385 390 395 400 405 410 415 420 425 430 435 440 445 450 455 460 465 470 475 480 485 490 495 500 505 510 515 520 525 530 535 540 545 550 555 560 565 570 575 580 585 590 595 600 605 610 615 620 625 630 635 640 645 650 655 660 665 670 675 680 685 690 695 700 705 710 715 720 725 730 735 740 745 750 755 760 765 770 775 780 785 790 795 800 805 810 815 820 825 830 835 840 845 850 855 860 865 870 875 880 885 890 895 900 905 910 915 920 925 930 935 940 945 950 955 960 965 970 975 980 985 990 995 1000 1005 1010 1015 1020 1025 1030 1035 1040 1045 1050 1055 1060 1065 1070 1075 1080 1085 1090 1095 1100 1105 1110 1115 1120 1125 1130 1135 1140 1145 1150 1155 1160 1165 1170 1175 1180 1185 1190 1195 1200 1205 1210 1215 1220 1225 1230 1235 1240 1245 1250 1255 1260 1265 1270 1275 1280 1285 1290 1295 1300 1305 1310 1315 1320 1325 1330 1335 1340 1345 1350 1355 1360 1365 1370 1375 1380 1385 1390 1395 1400 1405 1410 1415 1420 1425 1430 1435 1440 1445 1450 1455 1460 1465 1470 1475 1480 1485 1490 1495 1500 1505 1510 1515 1520 1525 1530 1535 1540 1545 1550 1555 1560 1565 1570 1575 1580 1585 1590 1595 1600 1605 1610 1615 1620 1625 1630 1635 1640 1645 1650 1655 1660 1665 1670 1675 1680 1685 1690 1695 1700 1705 1710 1715 1720 1725 1730 1735 1740 1745 1750 1755 1760 1765 1770 1775 1780 1785 1790 1795 1800 1805 1810 1815 1820 1825 1830 1835 1840 1845 1850 1855 1860 1865 1870 1875 1880 1885 1890 1895 1900 1905 1910 1915 1920 1925 1930 1935 1940 1945 1950 1955 1960 1965 1970 1975 1980 1985 1990 1995 2000 2005 2010 2015 2020 2025 2030 2035 2040 2045 2050 2055 2060 2065 2070 2075 2080 2085 2090 2095 2100 2105 2110 2115 2120 2125 2130 2135 2140 2145 2150 2155 2160 2165 2170 2175 2180 2185 2190 2195 2200 2205 2210 2215 2220 2225 2230 2235 2240 2245 2250 2255 2260 2265 2270 2275 2280 2285 2290 2295 2300 2305 2310 2315 2320 2325 2330 2335 2340 2345 2350 2355 2360 2365 2370 2375 2380 2385 2390 2395 2400 2405 2410 2415 2420 2425 2430 2435 2440 2445 2450 2455 2460 2465 2470 2475 2480 2485 2490 2495 2500 2505 2510 2515 2520 2525 2530 2535 2540 2545 2550 2555 2560 2565 2570 2575 2580 2585 2590 2595 2600 2605 2610 2615 2620 2625 2630 2635 2640 2645 2650 2655 2660 2665 2670 2675 2680 2685 2690 2695 2700 2705 2710 2715 2720 2725 2730 2735 2740 2745 2750 2755 2760 2765 2770 2775 2780 2785 2790 2795 2800 2805 2810 2815 2820 2825 2830 2835 2840 2845 2850 2855 2860 2865 2870 2875 2880 2885 2890 2895 2900 2905 2910 2915 2920 2925 2930 2935 2940 2945 2950 2955 2960 2965 2970 2975 2980 2985 2990 2995 3000 3005 3010 3015 3020 3025 3030 3035 3040 3045 3050 3055 3060 3065 3070 3075 3080 3085 3090 3095 3100 3105 3110 3115 3120 3125 3130 3135 3140 3145 3150 3155 3160 3165 3170 3175 3180 3185 3190 3195 3200 3205 3210 3215 3220 3225 3230 3235 3240 3245 3250 3255 3260 3265 3270 3275 3280 3285 3290 3295 3300 3305 3310 3315 3320 3325 3330 3335 3340 3345 3350 3355 3360 3365 3370 3375 3380 3385 3390 3395 3400 3405 3410 3415 3420 3425 3430 3435 3440 3445 3450 3455 3460 3465 3470 3475 3480 3485 3490 3495 3500 3505 3510 3515 3520 3525 3530 3535 3540 3545 3550 3555 3560 3565 3570 3575 3580 3585 3590 3595 3600 3605 3610 3615 3620 3625 3630 3635 3640 3645 3650 3655 3660 3665 3670 3675 3680 3685 3690 3695 3700 3705 3710 3715 3720 3725 3730 3735 3740 3745 3750 3755 3760 3765 3770 3775 3780 3785 3790 3795 3800 3805 3810 3815 3820 3825 3830 3835 3840 3845 3850 3855 3860 3865 3870 3875 3880 3885 3890 3895 3900 3905 3910 3915 3920 3925 3930 3935 3940 3945 3950 3955 3960 3965 3970 3975 3980 3985 3990 3995 4000 4005 4010 4015 4020 4025 4030 4035 4040 4045 4050 4055 4060 4065 4070 4075 4080 4085 4090 4095 4100 4105 4110 4115 4120 4125 4130 4135 4140 4145 4150 4155 4160 4165 4170 4175 4180 4185 4190 4195 4200 4205 4210 4215 4220 4225 4230 4235 4240 4245 4250 4255 4260 4265 4270 4275 4280 4285 4290 4295 4300 4305 4310 4315 4320 4325 4330 4335 4340 4345 4350 4355 4360 4365 4370 4375 4380 4385 4390 4395 4400 4405 4410 4415 4420 4425 4430 4435 4440 4445 4450 4455 4460 4465 4470 4475 4480 4485 4490 4495 4500 4505 4510 4515 4520 4525 4530 4535 4540 4545 4550 4555 4560 4565 4570 4575 4580 4585 4590 4595 4600 4605 4610 4615 4620 4625 4630 4635 4640 4645 4650 4655 4660 4665 4670 4675 4680 4685 4690 4695 4700 4705 4710 4715 4720 4725 4730 4735 4740 4745 4750 4755 4760 4765 4770 4775 4780 4785 4790 4795 4800 4805 4810 4815 4820 4825 4830 4835 4840 4845 4850 4855 4860 4865 4870 4875 4880 4885 4890 4895 4900 4905 4910 4915 4920 4925 4930 4935 4940 4945 4950 4955 4960 4965 4970 4975 4980 4985 4990 4995 5000 5005 5010 5015 5020 5025 5030 5035 5040 5045 5050 5055 5060 5065 5070 5075 5080 5085 5090 5095 5100 5105 5110 5115 5120 5125 5130 5135 5140 5145 5150 5155 5160 5165 5170 5175 5180 5185 5190 5195 5200 5205 5210 5215 5220 5225 5230 5235 5240 5245 5250 5255 5260 5265 5270 5275 5280 5285 5290 5295 5300 5305 5310 5315 5320 5325 5330 5335 5340 5345 5350 5355 5360 5365 5370 5375 5380 5385 5390 5395 5400 5405 5410 5415 5420 5425 5430 5435 5440 5445 5450 5455 5460 5465 5470 5475 5480 5485 5490 5495 5500 5505 5510 5515 5520 5525 5530 5535 5540 5545 5550 5555 5560 5565 5570 5575 5580 5585 5590 5595 5600 5605 5610 5615 5620 5625 5630 5635 5640 5645 5650 5655 5660 5665 5670 5675 5680 5685 5690 5695 5700 5705 5710 5715 5720 5725 5730 5735 5740 5745 5750 5755 5760 5765 5770 5775 5780 5785 5790 5795 5800 5805 5810 5815 5820 5825 5830 5835 5840 5845 5850 5855 5860 5865 5870 5875 5880 5885 5890 5895 5900 5905 5910 5915 5920 5925 5930 5935 5940 5945 5950 5955 5960 5965 5970 5975 5980 5985 5990 5995 6000 6005 6010 6015 6020 6025 6030 6035 6040 6045 6050 6055 6060 6065 6070 6075 6080 6085 6090 6095 6100 6105 6110 6115 6120 6125 6130 6135 6140 6145 6150 6155 6160 6165 6170 6175 6180 6185 6190 6195 6200 6205 6210 6215 6220 6225 6230 6235 6240 6245 6250 6255 6260 6265 6270 6275 6280 6285 6290 6295 6300 6305 6310 6315 6320 6325 6330 6335 6340 6345 6350 6355 6360 6365 6370 6375 6380 6385 6390 6395 6400 6405 6410 6415 6420 6425 6430 6435 6440 6445 6450 6455 6460 6465 6470 6475 6480 6485 6490 6495 6500 6505 6510 6515 6520 6525 6530 6535 6540 6545 6550 6555 6560 6565 6570 6575 6580 6585 6590 6595 6600 6605 6610 6615 6620 6625 6630 6635 6640 6645 6650 6655 6660 6665 6670 6675 6680 6685 6690 6695 6700 6705 6710 6715 6720 6725 6730 6735 6740 6745 6750 6755 6760 6765 6770 6775 6780 6785 6790 6795 6800 6805 6810 6815 6820 6825 6830 6835 6840 6845 6850 6855 6860 6865 6870 6875 6880 6885 6890 6895 6900 6905 6910 6915 6920 6925 6930 6935 6940 6945 6950 6955 6960 6965 6970 6975 6980 6985 6990 6995 7000 7005 7010 7015 7020 7025 7030 7035 7040 7045 7050 7055 7060 7065 7070 7075 7080 7085 7090 7095 7100 7105 7110 7115 7120 7125 7130 7135 7140 7145 7150 7155 7160 7165 7170 7175 7180 7185 7190 7195 7200 7205 7210 7215 7220 7225 7230 7235 7240 7245 7250 7255 7260 7265 7270 7275 7280 7285 7290 7295 7300 7305 7310 7315 7320 7325 7330 7335 7340 7345 7350 7355 7360 7365 7370 7375 7380 7385 7390 7395 7400 7405 7410 7415 7420 7425 7430 7435 7440 7445 7450 7455 7460 7465 7470 7475 7480 7485 7490 7495 7500 7505 7510 7515 7520 7525 7530 7535 7540 7545 7550 7555 7560 7565 7570 7575 7580 7585 7590 7595 7600 7605 7610 7615 7620 7625 7630 7635 7640 7645 7650 7655 7660 7665 7670 7675 7680 7685 7690 7695 7700 7705 7710 7715 7720 7725 7730 7735 7740 7745 7750 7755 7760 7765 7770 7775 7780 7785 7790 7795 7800 7805 7810 7815 7820 7825 7830 7835 7840 7845 7850 7855 7860 7865 7870 7875 7880 7885 7890 7895 7900 7905 7910 7915 7920 7925 7930 7935 7940 7945 7950 7955 7960 7965 7970 7975 7980 7985 7990 7995 8000 8005 8010 8015 8020 8025 8030 8035 8040 8045 8050 8055 8060 8065 8070 8075 8080 8085 8090 8095 8100 8105 8110 8115 8120 8125 8130 8135 8140 8145 8150 8155 8160 8165 8170 8175 8180 8185 8190 8195 8200 8205 8210 8215 8220 8225 8230 8235 8240 8245 8250 8255 8260 8265 8270 8275 8280 8285 8290 8295 8300 8305 8310 8315 8320 8325 8330 8335 8340 8345 8350 8355 8360 8365 8370 8375 8380 8385 8390 8395 8400 8405 8410 8415 8420 8425 8430 8435 8440 8445 8450 8455 8460 8465 8470 8475 8480 8485 8490 8495 8500 8505 8510 8515 8520 8525 8530 8535 8540 8545 8550 8555 8560 8565 8570 8575 8580 8585 8590 8595 8600 8605 8610 8615 8620 8625 8630 8635 8640 8645 8650 8655 8660 8665 8670 8675 8680 8685 8690 8695 8700 8705 8710 8715 8720 8725 8730 8735 8740 8745 8750 8755 8760 8765 8770 8775 8780 8785 8790 8795 8800 8805 8810 8815 8820 8825 8830 8835 8840 8845 8850 8855 8860 8865 8870 8875 8880 8885 8890 8895 8900 8905 8910 8915 8920 8925 8930 8935 8940 8945 8950 8955 8960 8965 8970 8975 8980 8985 8990 8995 9000 9005 9010 9015 9020 9025 9030 9035 9040 9045 9050 9055 9060 9065 9070 9075 9080 9085 9090 9095 9100 9105 9110 9115 9120 9125 9130 9135 9140 9145 9150 9155 9160 9165 9170 9175 9180 9185 9190 9195 9200 9205 9210 9215 9220 9225 9230 9235 9240 9245 9250 9255 9260 9265 9270 9275 9280 9285 9290 9295 9300 9305 9310 9315 9320 9325 9330 9335 9340 9345 9350 9355 9360 9365 9370 9375 9380 9385 9390 9395 9400 9405 9410 9415 9420 9425 9430 9435 9440 9445 9450 9455 9460 9465 9470 9475 9480 9485 9490 9495 9500 9505 9510 9515 9520 9525 9530 9535 9540 9545 9550 9555 9560 9565 9570 9575 9580 9585 9590 9595 9600 9605 9610 9615 9620 9625 9630 9635 9640 9645 9650 9655 9660 9665 9670 9675 9680 9685 9690 9695 9700 9705 9710 9715 9720 9725 9730 9735 9740 9745 9750 9755 9760 9765 9770 9775 9780 9785 9790 9795 9800 9805 9810 9815 9820 9825 9830 9835 9840 9845 9850 9855 9860 9865 9870 9875 9880 9885 9890 9895 9900 9905 9910 9915 9920 9925 9930 9935 9940 9945 9950 9955 9960 9965 9970 9975 9980 9985 9990 9995 10000 10005 10010 10015 10020 10025 10030 10035 10040 10045 10050 10055 10060 10065 10070 10075 10080 10085 10090 10095 10100 10105 10110 10115 10120 10125 10130 10135 10140 10145 10150 10155 10160 10165 10170 10175 10180 10185 10190 10195 10200 10205 10210 10215 10220 10225 10230 10235 10240 10245 10250 10255 10260 10265 10270 10275 10280 10285 10290 10295 10300 10305 10310 10315 10320 10325 10330 10335 10340 10345 10350 10355 10360 10365 10370 10375 10380 10385 10390 10395 10400 10405 10410 10415 10420 10425 10430 10435 10440 10445 10450 10455 10460 10465 10470 10475 10480 10485 10490 10495 10500 10505 10510 10515 10520 10525 10530 10535 10540 10545 10550 10555 10560 10565 10570 10575 10580 10585 10590 10595 10600 10605 10610 10615 10620 10625 10630 10635 10640 10645 10650 10655 10660 10665 10670 10675 10680 10685 10690 10695 10700 10705 10710 10715 10720 10725 10730 10735 10740 10745 10750 10755 10760 10765 10770 10775 10780 10785 10790 10795 10800 10805 10810 10815 10820 10825 10830 10835 10840 10845 10850 10855 10860 10865 10870 10875 10880 10885 10890 10895 10900 10905 10910 10915 10920 10925 10930 10935 10940 10945 10950 10955 10960 10965 10970 10975 10980 10985 10990 10995 11000 11005 11010 11015 11020 11025 11030 11035 11040 11045 11050 11055 11060 11065 11070 11075 11080 11085 11090 11095 11100 11105 11110 11115 11120 11125 11130 11135 11140 11145 11150 11155 11160 11165 11170 11175 11180 11185 11190 11195 11200 11205 11210 11215 11220 11225 11230 11235 11240 11245 11250 11255 11260 11265 11270 11275 11280 11285 11290 11295 11300 11305 11310 11315 11320 11325 11330 11335 11340 11345 11350 11355 11360 11365 11370 11375 11380 11385 11390 11395 11400 11405 11410 11415 11420 11425 11430 11435 11440 11445 11450 11455 11460 11465 11470 11475 11480 11485 11490 11495 11500 11505 11510 11515 11520 11525 11530 11535 11540 11545 11550 11555 11560 11565 11570 11575 11580 11585 11590 11595 11600 11605 11610 11615 11620 11625 11630 11635 11640 11645 11650 11655 11660 11665 11670 11675 11680 11685 11690 11695 11700 117

1002'114



1002514



Редактор Н. Шендкая Составитель И. Кетков
 Техрай К. Мамболо Корректор С. Шекар
 Заказ 1484/3 Тираж 601 Пожарское
 ВНИИПИ Государственного комитета СССР
 по делам изобретений и открытий
 113035, Москва, Ж-35, Раушская наб., д. 4/5
 Филиал ВПИ "Патент", г. Ужгород, ул. Проектная, 4

15/09 '00 VRI 12:58 [TX/RX NR 84301]

STANDARD 11

15/09 '00 VRI 14:24 FAX 31 70 378141

BEST AVAILABLE COPY

[Translator's Note: Original Russian was very blurred. Guesses and other uncertainties marked by [?] when appropriate.]

Union of Soviet Socialist Republics	SPECIFICATION OF INVENTOR'S CERTIFICATE	(11) 1002514
[State Seal]	(61) Inventor's certificate of addition —	
	(22) Applied November 9[?], 1981 (21) 3352116/22-03 with the attachment of application No. -	(51) Int. Cl. ³ E 21 D[?] 29/10
USSR State Committee on Inventions and Discoveries	(23) Priority - Published March 7, 1983, Bulletin No. 9 Publication date of specification January[?] 7, 1983[?]	(53) UDC 622.249.4 (088.8)
(72) Inventors	V. ?. Masich[?], A. A. Tsybin, A. A. Gaigorovskiy[?], [illegible], and V. V. [illegible, might be Toropynin]	
(71) Applicant	All-Union [illegible line]Scientific-Research Institute of Drilling Technology	

(54) A DEVICE FOR PLACING A PATCH IN A WELL

1

The invention relates to drilling and operation of oil and gas wells, and specifically to devices that can be used for sealing locations of damage to the casing or a fluid loss zone.

A device is known for placing a patch in a casing, including a [illegible, might be corrugation or corrugated] patch and [illegible, might be "securing at the lower end"] [illegible] hydraulic coring head [illegible, might be "with guide [illegible] and conical ram"] [1].

However, the use of the aforementioned device is associated with significant difficulties in the manufacture of the corrugated pipes for the patch and placing the patches downhole. The latter is explained by the fact that if the strength of preliminary bonding of the patch to the string is insufficient, during pulling the corrugated patch [illegible] may shift and the location of the damage will remain unsealed.

The device closest to the invention is a device for placing a patch in a well that includes a hollow perforated body with an elastic tubular element secured thereon, a patch to be expanded, and a

locking assembly to keep the patch from moving longitudinally [2].

A disadvantage of that device is the poor reliability in operation, associated with problems in the design of the patch locking assembly. This may lead to incomplete pressing of the patch and jamming of the entire device in the well.

The aim of the invention is to improve the reliability of operation of the device.

The aforementioned aim is achieved by the fact that in the device for placing a patch downhole, including a hollow perforated body with an elastic tubular element secured thereon, a patch to be expanded, and a locking assembly to keep the patch from moving longitudinally, the latter is implemented as spring-controlled stops and a bushing secured within the body by shear pins, with a seat for a ball that will be dropped and recesses on the outer surface, where the body has radial through holes for disposition therein of the spring-controlled stops, mounted in the plane of the recesses in the bushing.

Fig. 1 shows a general view of the device in the run-in position; Fig. 2 shows the A—A section in Fig. 1;

Fig. 3 shows the B—B section in Fig. 1; Figs. 4 and 5 show the device in the working position; Fig. 6 shows the same, after the work is completed.

The device (Fig. 1) consists of a composite hollow perforated body 1 with an elastic tubular element 2 slipped onto it. On top of elastic element 2 is placed the patch 3 to be expanded, fabricated from corrosion-resistant metal having the required strength and elastic properties, such as stainless steel.

Elastic tubular element 2 is secured to body 1 with the help of sleeve coupling 4. In the upper portion of body 1, there is a thread for joining [illegible] 5. The lower portion of the composite body, having radial holes *a* and *b*, [two illegible words] cap 6 with calibrated orifice *c*.

The locking assembly to keep patch 3 from moving longitudinally is implemented as bushing 7 with seat *d*, recesses *e* and [illegible-2 words] *f* on the outer surface. Stops 8, provided with springs 9, are disposed in through holes *b* of body 1. Patch 3 is supported[?] on stops 8 as the device is lowered downhole. Bushing 7 is restrained from unintended movement by shear bolt 10. Shear member 11, mounted in the lower portion of body 1, serves as a limit stop to limit movement of bushing 1.

The device operates as follows.

After the device is lowered downhole on drill pipes or tubing to the required depth, ball 12 is tossed into the pipe and lands in seat *d* of bushing 7, and closes off the central channel therein (Fig. 4). Under the action of the pressure of the injected fluid, elastic element 2 expands and makes contact with patch 3. When a certain pressure is reached in the internal cavity of the pipes and elastic element 2, patch 3 is deformed and squeezed against the wall of the well, sealing off the location of damage to the casing or the fluid loss zone. In the case when damage to the casing is to be repaired, at the ends of sleeve 3, rubber packing rings are placed in the bores to ensure leaktightness of the patch.

After the section of patch 3 in contact with the working part of elastic element 2 has been squeezed against the wall of the well, the pressure of the fluid in the pipes is increased up to the value at which shear bolt 10 fails. Then bushing 7 moves downward as far as it will go toward shear

member 11 (Fig. 5). Premature shearing off of member 11 on movement of bushing 7 is prevented because throttling of the fluid displaced from body 1 by moving bushing 7 through calibrated orifice *b* in cap 6 creates a hydraulic shock absorber, which ensures smooth movement of bushing 7 without jarring. In this position of bushing 7 (Fig. 5), recesses *e* are against stops 8. Under the action of springs 9, stops 8 move inside body 1 and drop into recesses *e* of bushing 7 (Fig. 5). In order to deform and tightly squeeze the lower part of patch 3 against the wall of the well, the pressure in the pipes is released, elastic tubular element 2 takes on its original shape, then the device is lowered by a certain amount. By heating the fluid in the pipe and raising its pressure up to the known limit, the lower part of patch 3 is deformed. After the operation of placing the patch is completed and before lifting the tool to the surface, the pressure of the fluid in the pipes is raised until bolt 10 shears off, at which point bushing 7 moves to the extreme lower position (Fig. 6). Slot *f* in bushing 7 matches radial hole *a* in body 1 and the inner cavity of the pipes communicates with the casing string—borehole annular space, which ensures draining of the tubes when the tool is lifted. Stops 8 remain in a position for which the tool can be lifted unhindered to the surface. The device is prepared for carrying out the next operations of placing patches downhole by moving bushing 7 to the extreme upper position and replacing shear members 10 and 11 with new ones. For convenience of assembly, member 10 can be mounted in body 1 under bushing 7.

Patch 3 is restrained during lowering of the tool downhole with the help of the assembly (elements 7-9) disposed in the lower portion of body 1 (Fig. 1), being the optimal embodiment. In addition to the aforementioned, two assemblies may be used, identical in design and disposed in the upper and lower portion of body 1. An embodiment of the restraint of sleeve 3 is also possible for which the described assembly is used, disposed in the lower part of the body, and the breakable pin that locks sleeve 3 is disposed in its upper part. Fracture of the pin and release of sleeve 3 may be accomplished either by deformation of elastic element 2 or by moving bushing 7.

Use of the proposed device makes it possible to improve the reliability of operation for elimination of leaks in the string or a fluid loss zone by preventing poor quality bonding of the patch of the device to the walls of the well. Furthermore, it eliminates the need to fabricate expensive corrugated patches on special equipment.

Thus the technical and economic impact from using the proposed device [several illegible words], consumed in elimination of leaks in the string or a fluid loss zone [illegible].

Claim

A device for placing a patch in a well, including a hollow

perforated body with an elastic tubular element secured thereon, a patch to be expanded, and a locking assembly to keep the patch from moving longitudinally, *distinguished by the fact that*, with the aim of improving its reliability in operation, the locking assembly to keep the patch from moving longitudinally is implemented as spring-controlled stops and a bushing, secured within the body by shear pins, with a seat for a ball that will be dropped and recesses on the outer surface, where the body has radial through holes for disposition therein of the spring-controlled stops, mounted in the plane of the recesses in the bushing.

Information sources considered in the examination

1. US Patent No. 3179168, cl. 166-14[?], published 1965.
2. US Patent No. 3111991, cl. 166-14[?], published 1963 (prototype).

TRANSLATOR'S NOTE:

Cyrillic letters are placed on these figures to identify certain parts, but the blurred copy made it impossible to locate most of them for translation. Here is a key for the Russian letters and their English equivalents used in the translation of the text:

а	б	в	г	д	е
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>

[figures under columns 5 and 6]

[see Russian original for figure]

[see Russian original for figure]

Fig. 1

A-A

c[?]

f[?]

Fig. 2

[see Russian original for figure]

[see Russian original for figure]

$c[?]$

$B-B$

$b[?]$

Fig. 3

Fig. 4

[see Russian original for figure]

[see Russian original for figure]

Fig. 5

Fig. 6

Editor [illegible]	Compiler [illegible] Tech. Editor [illegible]	Proofreader S. Shekmar[?]
Order 1484/3 [?]	Run 601	Subscription edition

All-Union Scientific Research Institute of Patent Information and Technical and Economic
Research of the USSR State Committee on Inventions and Discoveries [VNIPI]
4/5 Raushkaya nab., Zh-35, Moscow 113035

Affiliate of "Patent" Printing Production Plant, Uzhgorod, 4 ul. Proektnaya



AFFIDAVIT OF ACCURACY

I, Kim Stewart, hereby certify that the following is, to the best of my knowledge and belief, true and accurate translations performed by professional translators of the following Patents and Abstracts from Russian to English:

ATLANTA	<i>Patent 1786241 A1</i>
BOSTON	<i>Patent 989038</i>
BRUSSELS	<i>Abstract 976019</i>
CHICAGO	<i>Patent 959878</i>
DALLAS	<i>Abstract 909114</i>
DETROIT	<i>Patent 907220</i>
FRANKFURT	<i>Patent 894169</i>
HOUSTON	<i>Patent 1041671 A</i>
LONDON	<i>Patent 1804543 A3</i>
LOS ANGELES	<i>Patent 1686123 A1</i>
MIAMI	<i>Patent 1677225 A1</i>
MINNEAPOLIS	<i>Patent 1698413 A1</i>
NEW YORK	<i>Patent 1432190 A1</i>
PARIS	<i>Patent 1430498 A1</i>
PHILADELPHIA	<i>Patent 1250637 A1</i>
SAN DIEGO	<i>Patent 1051222 A</i>
SAN FRANCISCO	<i>Patent 1086118 A</i>
SEATTLE	<i>Patent 1749267 A1</i>
WASHINGTON, DC	<i>Patent 1730429 A1</i>
	<i>Patent 1686125 A1</i>
	<i>Patent 1677248 A1</i>
	<i>Patent 1663180 A1</i>
	<i>Patent 1663179 A2</i>
	<i>Patent 1601330 A1</i>
	<i>Patent SU 1295799 A1</i>
	<i>Patent 1002514</i>

PAGE 2

AFFIDAVIT CONTINUED

(Russian to English Patent/Abstract Translations)

Kim Stewart

Kim Stewart

TransPerfect Translations, Inc.

3600 One Houston Center


1221 McKinney

Houston, TX 77010

Sworn to before me this
9th day of October 2001.

Maria A. Serna

Signature, Notary Public



Stamp, Notary Public

Harris County

Houston, TX